

XXXXXX
FEET

Relative to the compass bearing of the random line, the true line from the 1/4 cor. Secs. 24 & 25 to the cor. of Secs. 24, 25, 19 and 30 bears S 89°44' E, a distance of 2622.4 feet.

Beginning new measurement

1311.2

Point for East 1/16 corner between Secs. 24 & 25. Adjustment from temp. stake 3960. South 16.8 feet, West 13.4 feet.

1/16 COR.
24, 25
1. N. 6.

Set an iron pipe 1 1/2 inches in diameter, 3 feet long, filled with charcoal with an Oregon State Board of Forestry bronze cap stamped E 1/16 S24 S25 1949, 199

from which:

A cedar snag, 3 1/4 inches in diameter, bears N 24° E, a distance of 16.3 feet. Scribed E 1/16 S24 199.

A metal location poster on a cedar snag, 30 inches in diameter, bears N 24° E, a distance of 16.3 feet and marked S24, 25, TLN R6W, E 1/16 cor. 16.3 feet S 24° W.

Placed a mound of stone around iron pipe.

2622.4

The cor. to Secs. 24, 25, 19 and 30, TLN, R 5 & 6 W.

The above work done by Don Davis, Transitman, Wayne Frank, Bruce Thomas, Chainmen, under my direction.

Lyle E. Beyers
Lyle E. Beyers
Forest Engineer

