

1911
TILLAMOOK COUNTY

temporary center of section. For the center of section we place a concrete pedestal 12" square at top, 18" square at bottom and 36" high, set 30 inches in the ground, with a 2 1/2" brass disc on which is stamped a circle and the number 3 and, circumferentially, CEN. SEC. T. 3 N. R. 6 W.W.M. - O.S.H.D. We also set a 4"X 4" white guard post stenciled CENTER SEC. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black. No live trees available for bearing trees.

39+83.6 3/4"X 30 " iron pin for the East 1/16 corner on the E.& W. centerline of the section, with 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

52+95.9 The quarter corner on the line between sections 3 and 2, previously described.

Returning to the South 1/16 corner on the N.& S. centerline of section 3.

Thence N. 89° 19 1/2' W. toward the center of the S.W. quarter of Sec. 3.

13+32.9 3/4"X 30" iron pin for the center of the S.W. 1/4 of section 3, with 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

Thence N. 0° 19' W. between the East and West halves of the S.W. quarter of section 3.

13+24.5 The West 1/16 corner on the E.& W. centerline of the section.

Returning to the North 1/16 corner on the N.& S. centerline of section 3, we ran thence,

S. 89° 21 1/2' E. between the North and South halves of the N.W. quarter of section 3.

13+12.1 3/4"X 30" iron pin for the center of the N.W. 1/4 of section 3, with a 4"X 4" white guard post stenciled 1/16 SEC. COR. on 2 faces and O.S.H. PROP. COR. on other 2 faces in black.

26+24.2 The North 1/16 corner on the line between sections 3 and 2, previously

How
NW 1/6 COR.
NE 1/6 COR.

From the corner to sections 32-33-5-4 on the line between townships 3 and 4 North, R. 6 W., previously described, we ran Southerly by traverse to the quarter corner between sections 5 and 4.

At a point 2151.9 ft. S. 0° 16' W. of the section corner, in a small area untouched by fire, we found an old 4"X 4" scribed stake still in place, and both original bearing trees at proper distances. Scribing shows plainly but both trees dead. We replace the stake with a 2"X 48" galv. iron pipe with brass cap on which is stamped a line with short cross mark and, circumferentially, 1/4 COR. T. 3 N. R. 6 W.W.M. - O.S.H.D. We also set a 4"X 4" white guard post stenciled 1/4 SEC. COR. on 2 faces in black and marked 2 new bearing trees, as follows:

- An 18" hemlock bears S. 11° W. 80.0 ft., scribed 1/4 S. B.T.
- A 14" cedar bears S. 38° E. 58.0 ft., scribed 1/4 S. B.T.