

Cour Surveyor's Record, Tillamook Cour Oregon

235  
235

SECTION 31, T3N, R9W. REWITNESSED & RESET CORNERS.

CHAINS

SECTION CORNER 29-30-31-32. RE WITNESSED.

Found the original hemlock BT for Section 29. dead and down; original hemlock BT for Section 30 a dead stub, but marks plain. Measuring from the CENTER of this BT, s40°E 12.0 feet, set a 3/4" iron pipe for corner; from this placed a yellow metal location poster S 53°E 9.4 feet; scribed new BTs:

Hemlock 14" S64°W 41.0 feet horizontal to tree center;  
Hemlock 8" N49°W 15.7 " "

SECTION CORNER 30-31, T3N, R9W, and 25-36, T3N, R10W.

On Range Line. Reset by single proportion, North 5318.2 feet, and West 56.3 feet from the SW corner of T3N, R9W. Set a 1 1/2" iron pipe, made 2 new BTs:

Hemlock 5", S86°W, 12.6 feet to center. SEE PAGE-218  
Alder 10", N29°E, 25.2 " " ?

Yellow metal location poster on 3" willow, 955 feet south.

Found a cruiser's mark, said to be that of W. S. Cone, or Wm. Reifenberg, who later used the same mark, about 10 feet SE and facing new corner.

1/2 Corner, Sections 36/31, T3N, R 9 and 10 W, Reset by single proportion, 1/2 of North and West distances as above for Section Corner. Set a 1 1/2" iron pipe in top of an old 4' fir stump; made new BTs:

Alder 4" N55°E 18.7 feet to center. SEE PAGE 218  
Alder 4" N86°W 19.1 " " ?

1/4 Corner. Sections 30/31, T3N, R9W, Reset by proportion, from NE corner of Section 31, as found, see above, and NW corner of Section 31, as reset, see above.

Set a 3/4" iron pipe, tall stake, made new BTs:

Alder 10" S26°E 7.7 feet to center.  
Alder 9" N26°W 6.8 " "

Done February and April, 1955. Traverses by transit and steel tape. Done in presence of Worth Williamson, employee of Crown-Zellerbach Corp., and Robert Walker, of Mohler, Oregon.

W. A. Markham  
Registered Engineer #1842.



Book I

235

235