

County Surveyor's Record, Tillamook County, Oregon

238 8

T 3 S, R 9 W.

Rewitnessed Corners

Mervin Whitmore, U.S. Forest Service

<p>16/15 Sec. Cor. $\frac{16}{21} \frac{15}{22}$</p>	<p>Set a post from which A 36" fir bears N 28°20' W 130 lks. Large Scar in bark. A 30" dead fir snag bears N 74°E 71 lks mkd. T3S R9W S15BT. A 30" dead fir snag bears S 70°E 68 lks. not 125 lks as recorded in field notes. Mkd. T3S R9W (balance rotted off) A 16" fir bears S 70°E 35 feet slope distance mkd. T3S R9W S22BT (new BT).</p> <p>In the presence of Wm. H. Balmer & Joe Bonin. May 23, 1955.</p>
<p>c.c. Sec. Cor $\frac{1}{21}$</p>	<p>Set a post from which A dead fir 18" bears S 47°E 14 lks. scribing visible (old BT) A 6" hemlock dead and fallen bears S 35°W 11 lks under large fallen cedar tree. Shows old ax marks but scribing rotted off (old BT) A 24" fir bears S 59°W 27 feet maked T3S R9W S2BT (new BT) A 18" hemlock bears S 15°E 21.3 feet mkd. T3S R9W S1BT (New BT)</p> <p>In the presence of Martin Chaffee and Ray McKnight. June 14, 1955.</p>
<p>$\frac{1}{4}$ Sec. Cor $\frac{28}{33}$</p>	<p>Set a 3/4" pipe from which A dead fir snag 41" bears S 45°W 18 lks. distance mkd. $\frac{1}{4}$S 33 BT (old BT) A fir 16" bears N 52°E 13 1/2 feet slope distance mkd. $\frac{1}{4}$S 28 BT (new BT)</p> <p>In the presence of Robert Johnson (B.L.M. forester). Nov. 17, 1954.</p>
<p>Twsp. Cor. T3S $\frac{36}{16} \frac{31}{R9W}$ T4S</p>	<p>Set a 1 1/4" pipe 30" above ground for township corner, from which A dead fir snag 30" bears N 26°E 110 lks. with old scribing visible but hardly legible (old BT) The remains of the other three old BTs are rotted snags and stumps; all marks rotted off. A 14" alder bears N 58°W 5 feet mkd. T3SR9WS36BT (new BT) A 36" fir bears S 39°E 49 feet mkd. T4SR8WS6BT (new BT) A 20" fir bears S 70°W 68 feet slope distance mkd. T4SR9WS1BT (new BT)</p> <p>In the presence of Thomas Nicklaus. June 16, 1955</p>
<p>R9W</p>	

Book I