

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
(See official plat)
Closing corner common to Sections 7 and 18, T1S,
R7W, W.M., Tillamook County, Oregon.

ORIGINAL

Closing corner bears S88° 10' 34" W 18.7 ft.; see records for restoration.
(Marked original closing corner pipe, AM -- amended monument -- and
scribed bearing trees for same, AM)

ESTABLISHED

Var. 21½E

At the point of intersection of the true range line and the Section line
7 and 18 produced through the original closing corner set 1½" x 36"
galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF
FORESTRY T1S R8W R7W S12 S7 CC S18 1958 RS401", 33 inches in ground,
in mound of stone, and from which a:

50" Fir stump bears S59E 55.0 ft.; scribed T1S R7W S18 CC BT RS401.
78" Fir stump bears N53½E 73.4 ft.; scribed T1S R7W S7 CC BT.

Oregon State Board of Forestry metal location poster on 50" Fir stump BT.
Set 4" x 4" x 50" white painted Cedar post 1.0' S.E. of pipe.

Closing corner common to Sections 6 and 7, T1S,
R7W, W.M., Tillamook County, Oregon.

ORIGINAL

Closing corner pipe bears N83° 44' 04" E 7.8 ft.; see records for
restoration. (Scribed 50" Fir snag bearing tree, AM -- amended
monument)

ESTABLISHED

Var. 21½E


At the point of intersection of the true range line and a line projected
over the original closing corner from the one quarter corner to
sections 6 & 7 set 1½" x 36" galvanized iron pipe with 3" bronze cap
marked "OREGON STATE BOARD OF FORESTRY T1S R8W R7W S1 S6 CC S7 1958
RS401", 33 inches in ground, in mound of stone, and from which a:

3" Fir bears N58E 29.2 ft.; scribed X B.T.
72" Fir stump bears S26E 117.1 ft.; scribed T1S R7W S7 CC BT RS401.


Oregon State Board of Forestry metal location poster on 3" Fir BT.
Set 4" x 4" x 52" white painted Cedar post 0.8' S.W. of pipe.

Dated December 17, 1958

Established by



Richard A. Morris



Present and witnessed by R. Schulson
H. Russell
R. Cop