

CHAINS

RE-ESTABLISHED CORNERS FOR STATE OF OREGON-DEPARTMENT OF FORESTRY
(See official plat)

One Quarter corner common to Sections 16 and 17, T3S, R8W, W.M.,
Tillamook County, Oregon.

CORRECTION REPORT

No evidence of original corner found

RE-ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY 1/4 S17 S16 1961 RS401", 32 inches in ground, and
from which a:

42" Fir bears S79 1/2 W 23.8 ft.; scribed 1/4 S17 BT.
7" Fir bears N41 E 15.4 ft.; scribed 1/4 S16 BT RS401.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. S.E. of corner pipe.
Oregon State Forestry Department metal location poster on 7" Fir BT.

Var. 21 1/2 E

One Quarter corner common to Sections 21 and 22, T3S, R8W,
W.M., Tillamook County, Oregon.

No evidence of original corner found.

RE-ESTABLISHED

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY 1/4 S21 S22 1961 RS401", 33 inches in ground, and
from which a:

36" Spruce growing over a log bears N82 1/2 E 68.2 ft.; scribed 1/4 S22 BT.
30" Fir bears N57 W 72.6 ft.; scribed 1/4 S21 BT RS401.


Set 4" x 4" x 52" white painted Cedar post 1.0 ft. N. of corner pipe.
Oregon State Forestry Department metal location poster on 36" Spruce BT.

Dated January 22, 1962

Re-established by



Richard A. Morris



Present and witnessed by G. E. Nylund
A. Duncan

1/4 Cor.
W.M. 16
S. 81

1/4 Cor.
W.M. 21
S. 81

197