

(contd,) County Surveyor's Record, Tillamook County, Oregon

T4.SR.9W

Rewitnessed corners Leonard Whitmore, U.S. Forest Service

22 Closing corner for secs. 22-27 West boundary
 Original stone (beneath a 40 in. fallen snag) mkd. 27 on S.E.
 and 22 on N.E. faces.
 27 14 in. fir, S. 40° E., 7 ft. mkd. S22BT (new BT)
 18 in. fir N. 24° E., 17 ft. mkd. S22BT (new BT)

In the presence of Mervin Whitmore, February 11, 1961

*

28 N. E. Corner of section 28
 Original stone with 4 notches on N. and 2 notches on S. edges
 12 in. fir S. 41° W., 11½ ft. mkd. S 28 BT (new BT)

In the presence of Mervin Whitmore, February 11, 1961

¼ cor. Original post with stone mound at base.
 22 23 12 in. fir, S. 31° 30' W., 57 ft. mkd. ¼ S22BT (new BT)
 12 in. fir S. 5° E., 25½ ft. mkd. ¼ S23BT (new BT)
 By Mervin Whitmore, April 8, 1961

¼ cor. Set a 4"x4"x36" fir limb with a rock mound at base.
 7 8 9 in. fir, N. 15° W., 55 ft. mkd. ¼ S7BT (new BT)
 14 in. fir, N. 40° 30' E., 65 ft. mkd. ¼ S8BT (new BT)

By Mervin Whitmore, April 8, 1961

¼ cor. Set a 4"x4"x24" fir limb for corner
 19 20 12 in. fir, N. 21° W., 47½ ft. mkd. ¼ S19BT (new BT)
 16 in. fir, S. 8° E., 19 ft. mkd. ¼ S20BT (new BT)

By Mervin Whitmore, March 28, 1961

¼ cor. Set 1½ in. pipe, 2½ ft. above ground
 20 21 50 in. snag N. 62° 15' E., 11 ft. (original)
 20 in. alder S. 30° 30' W., 31 ft. (original)
 In the presence of Mervin Whitmore, March 25, 1961

Sec. Cor. Closing corner south boundary between secs. 20-21
 20 21 Set a fir limb
 16 in. fir, N. 30° W., 62 ft mkd. CCT4SR9WS20BT (new BT)
 18 in. fir, N. 61° 30' E., 114 ft mkd. CCT4SR9WS21BT (new BT)
 Corner is located on an open Salal flat 164 ft. west of
 common corner to secs. 28-29

In the presence of Mervin Whitmore, March 25, 1961

Pg - 2 of 5 M. Whitmore