

CHAINS  
FEET

Survey for the Oregon State Board of Forestry of the Section line between Sections 22 & 27, T 2N, R 6W, W.M., Tillamook & Washington Counties, Oregon

RETRACEMENT:

Beginning at the section corner to sections 21-22-27 & 28 determined from the original bearing trees

A Hemlock tree, 36" in diameter, bears N 61° E, a distance of 20.5 feet; scribed T 2N, R 6W, S 22; BT scribed on lower blaze.

A fir stump, 38" in diameter, bears N 39° W, a distance of 23.3 feet. (This distance does not correspond with the call of the original field notes which gives 10.6 feet as the distance.)

A hemlock tree bears S 30° W, a distance of 39.1 feet (the call of the original field notes describes this BT as bearing S 46° 30' W, a distance of 10.6 feet), scribed T 2N, R 6W, other scribe marks illegible.

The roots of a hemlock bear S 39° E, a distance of 15.8 feet.

At the corner point

Set a 1½" iron pipe, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped:

T 2N, R 6W, S 21 S 22 S 27 S 28 1949 199

from which:

A hemlock tree, 32" in diameter, bears S 30° E, a distance of 25.9 feet, scribed T 2N, S 27 199.

Starting with a compass bearing using a K. & E Light Mtn. Transit, I run East on a random line between sections 22 & 27

486.7

Road runs NW SE

2640.0

Set temp stake. No evidence of 1/4 cor. found

3257.8

Begin to ascend ridge.

3239.8

Road runs NW SE

4518.6

Top of ridge runs NW SE

5656.2

The section corner common to Secs 23 & 26 bears S 80° 07' E, a distance of 122.3 feet determined from the remains of the original bearing trees.

A stump hole of a down up-rooted hemlock, 24" in diameter bears S 50° E, a distance of 17.3 feet. On an old face, 2" deep; found parts of the scribe marks remaining. The T is plainly visible but only parts of the R and the W remain.