

(41)

CHAINS FEET	
	<p>SURVEY OF THE SECTION LINE BETWEEN SECTIONS 23 & 26 AND BETWEEN SECTIONS 22 & 27 T1N R6W FOR OREGON STATE BOARD OF FORESTRY.</p> <p>RETRACEMENT:</p> <p>Beginning at a point which bears S 36° E, a dist. of 23 feet from the cor. of Secs. 23, 24, 25 & 26 T1N R6W previously determined and reestablished by an iron pipe and bronze cap stamped T1N S23 S24 S25 S26 R6W 1949 199.</p> <p>Starting with a compass bearing, variation 22° E, using a K & E Light Mtn Transit West on a random line between Secs. 23 & 26.</p>
Random Line Dist., feet	
650.1	Road on a curve running SW & NW.
1780.7	Summit of a flat topped ridge.
2640.0	Nearby found a stone 11x8x7 inches, with 1/4 chiseled on the exposed face, which undoubtedly had been moved from its original position by evidence of vegetation under the stone. Therefore, do not accept the stone as marking the point for corner.
3667.7	Head of spring; stream bears N 35° W.
3960.0	Set temp. stake.
4769.6	Stream, 2 feet wide, bears N 65° W.
5280	The cor. of Secs. 22, 23, 26 & 27 bears N 63° E, a distance of 38.2 feet.
	The corner determined by a squared 2x2 inch hemlock stake buried in the dirt but still erect in place.
	from which the remains of the original bearing tree:
	A stump hole of a down cedar, 12 inches in diameter, marked BT, bears S 35° E, a distance of 2.0 feet; the roots of the down cedar remain in the ground.
	No evidence of corner stone or hemlock BT found.
	Continue West on same line bet. Secs. 22 & 27. Begin new measurement.
426.3	Stream, 10 feet wide, bears N 30° E.
2448.2	Road running S-NE. Set stake on West side of road.
2657.2	Set temp. stake. No evidence of 1/4 cor. stone found.
	(Continued on page _____)