

(43)

CHAINS	
True line Distance, feet	
3924.3	<p>Point for the West 1/16 cor. between Secs. 23 & 26. Adjustment from temp. stake 3960. North 17.6 feet East 22.2 feet.</p> <p>Set an iron pipe, 1½ inches in diam., 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped W 1/16 S23, S26 1949 199.</p>
3965.3	<p>Set a 4" x 4" x 5' cedar post on true line at West side of road with a metal location poster marked Sec. 23/26, TLN, R6W, W 1/16 cor., 41 ft., West.</p>
5232.5	<p>To sec. cor. to Secs. 22, 23, 26 & 27 TLN R6W determined on retracement,</p> <p>Set an iron pipe, 1½ inches in diam., 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped TLN, R6W, S22, S23, S26, S27, 1949, 199.</p> <p>from which:</p> <p style="padding-left: 40px;">A fir snag, 50 inches in diam., bears S 67° W, a dist. of 22.4 feet. Scribed S27 199.</p> <p style="padding-left: 40px;">Placed a metal location poster on this snag marked Sec. 27, TLN, R6W, Sec. Cor. 22.4 feet, N 67° E.</p> <p>Relative to the compass bearing of the random line the true line bet. Secs. 22 & 27 bears S 89° 34' W. a distance of 5215.4 feet.</p>
True line Distance, feet	
2453.7	<p>Set a 4" x 4" x 5' cedar post on true line at E side of road with a metal location poster marked Sec. 22/27 TLN R6W 1/4 cor. 154 ft. West.</p>
2607.7	<p>Point for 1/4 cor. between Secs. 22 & 27. Adjustment from temp. stake - South 2.5 ft. East 83.6 ft.</p> <p>Set an iron pipe 1½ inches in diam., 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped 1/4 S22, S27 1949 199</p>

(Continued on page _____)