

CHAINS

SURVEY FOR THE OREGON STATE BOARD OF FORESTRY

Subdivision of Section 9, Twp. 1 N., Rge. 7 W. W.M.

Tillamook County, Oregon

Survey begun on April 14, 1950. Work carried on at intervals.
Completed January 10, 1951. A K & E light mtn. transit was
used, Variation 22° E.

RESURVEY OF EXTERIOR BOUNDARIES SECTION 9

Beginning at the corner to secs. 3, 4, 9 & 10.

S 0° 15' E on a random line between 9 & 10.

- 756.4 Set temporary stake on North edge of Wilson River highway.
 - 1320.0 Set temporary stake.
 - 1432.8 Stream, 12 feet wide, course West.
 - 2393.0 Swamp, 50 feet wide.
 - 2640.0 Set temporary stake.
 - 2995.0 Stream, 4 feet wide, course West.
 - 3937.2 Set temporary stake.
 - 4075.0 Gulch with stream, 4 feet wide, course NW.
 - 4761.8 Spur, sloping N 20° W.
 - 5279.1 The corner to sections 9, 10, 15, & 16 bears N 60° 30' W, a distance
of 59.7 feet.
- Adjustment to true line & setting of monuments.
- Relative to the compass bearing of the random line (S 0° 15' E)
the true line between sections 9 & 10, bears S 0° 19', a distance
of 5249.7 feet.
- The corner to sections 3, 4, 9, & 10 determined by
- A 18" x 10" x 5" stone, with 3 notches on East edge and five
notches on South edge, laying on bronze cap set in concrete
& stamped: T1N R7W 3 4 9 10 SECTION CORNER.
- from which:
- A maple, 30 inches in diam., bears S 45° W, a distance of 8.6
feet, recently scribed: BT S9.
 - A metal location poster on a maple sprout bears S 54° W, a
distance of 8.0 feet.
- S 0° 19' W.
- 756.4 Set a 4" x 4" x 4' cedar post on true line on North edge of Wilson
River Highway with a metal location poster marked: Sec 9/10
T1N R7W Sec 3-4-9-10 756.4 ft. North.