

CHAINS

A cedar snag, 50 inches in diam., bears S 55° E, a distance of 27.1 feet (41 lks).

(No evidence found of basalt stone.)

At the point for corner

Set a 1½ inch iron pipe, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped: TLN R7W S10 S15 S16 1950 199.

from which:

A fir, 8 inches in diam., bears N 47° E, a distance of 58.9 feet, scribed: S9 199.

A cedar, 58 inches in diam., bears S 04° 30' W, a distance of 86.6 feet scribed: TLN S16 199.

Placed a metal location poster on the 50 inch cedar & marked it: Sec 9, 10, 15 & 16 TLN R7W Sec Cor 27.1 ft. N 55° W.

Beginning at the corner to sections 8, 9, 16 & 17

S 88° 04' E on a random line between secs. 9 & 16.

173.0 Gulch, course S 85° W.

314.0 Fir snag, 60 inches in diameter.

1035.0 Spring, course North.

1169.1 Set temporary stake.

1712.5 Ridge, slopes N 60° W.

2624.8 Set temporary stake.

3114.7 Ridge, slopes N 60° W.

5342.0 The corner to sections 9, 10, 15 & 16 bears N 13° 46' E, a distance of 177.5 feet.

Adjustment to true line & setting of monuments.

Relative to the bearing of the random line, the true line between sections 9 & 16 bears S 89° 55' E, a distance of 5381.1 feet.

0 The corner to sections 8, 9, 16, & 17 determined by

A bronze cap set in concrete stamped; TLN R7W 8 9 17 16 SECTION CORNER, guarded by a 4 x 4 inch white cedar post marked: SHRW Sec 8 on NW side, Sec 9 on NE side, Sec 16 on SE side, & Sec 17 on SW side.

1345.3 Point for W 1/16 corner between sections 9 & 16 by proportionate distance.

Adjustment from temporary stake 1169.1 -- North 37.4 feet, East 176.9 feet.