

CHAINS

A fir snag, 56 inches in diam., bears N 34° E, a distance of 28.0 ft., scribed: ¼ S 4 199 BT.

Nailed a metal location poster on the 56 inch fir snag & marked it: Sec 4 T1N R7W ¼ cor 26.0 ft. S 34° W.

Piled a mound of stone around monument.

3994.3 Point for W 1/16 corner between sections 4 & 9 by proportionate distance.

Adjustment from temporary stake 3886.4 -- North 33.1 feet, West 109.2 feet.

At the point for corner

Set a 1½ inch iron pipe, 3 feet long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped: W 1/16 S4 S9 1951 199.

from which:

A fir snag, 69 inches in diam., bears N 20° E, a distance of 25.0 ft., scribed: W 1/16 S4 199 BT.

Placed a metal location poster on the 69 inch fir snag is marked: Sec 4 T1N R7W W 1/16 Cor 22.3 ft. S 20° W.

5325.8 Corner to sections 4, 5, 8 & 9 Township 1 North, Range 7 West determined by

A yew post, 5 inches in diam. 2½ feet above the ground, scribed: SC 9 on SE face, 8 on SW face, 4 on NE face, 5 on NW face.

from which:

A metal location poster on a 60 inch fir snag bears N 5° W approximately 65 feet, & marked: Sec 5/4 T1N R7W Sec Cor 65 Ft S 4° E.

SURVEY OF INTERIOR SECTION 9

Beginning at the ¼ cor. bet. secs 9 & 10.

S 89° 31' W on a random line through the center of sec. 9.

73.5 Stream, 3 feet wide, course N.W.

845.0 Stream, 10 feet wide, course North.

1300.7 Ridge, slopes North.

2465.3 Set temporary stake.

3553.9 Ridge, slopes N 20° W.

4106.5 Ridge, slopes N 20° W.  
Set temporary stake.

4217.4 Set temporary stake.

The ¼ cor. to secs. 8 & 9 bears N 85° 24' W a distance of 1147.9 ft.

Relative to the bearing of the random line, the true line through the center of sec. 9 bears N 89° 24' W, a distance of 5361.7 ft.