

CHAINS

Establishment of CN 1/16 Sec. 24.

The true line bet. center of Sec. 24 and the 1/4 cor. to 13, 24 bears N 02°55' W a distance of 2631.0.
Mean 1315.5.

1315.5 Point for CN 1/16 cor. Sec. 24.
Adjustment from temporary stake 3960.
South 19.6 feet West 200.2 feet.

Set an iron pipe $1\frac{1}{2}$ inches in diam., 3 ft. long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped: N 1/16 C-C, S24, 1949, 199.

from which:

A fir snag 48 inches in diam., bears N 9° W, a distance of 27 ft., scribed: BT N 1/16 S24 199.

A location poster, a fir snag 34 inches in diam., bears South a distance of 39.8 ft.

1707.6 Set a 4" x 4" x 5' white cedar post on South edge of Saddle Mtn. Road. Tag on post marked: Sec 24 T1N R6W CN 1/16 cor 392.1 ft. S 02°55' E.

Establishment of EC 1/16 cor. of Sec. 24.

The true line between the center of Sec. 24 and the 1/4 cor. to Secs. 24 & 19 bears N 88°29' E, a distance of 2600.9 feet.
Mean - 1300.4 ft.

Point for EC 1/16 cor. Sec. 24.
Adjustment from temporary stake 3960.
South 20.1 ft. West 106.6 ft.

Set an iron pipe $1\frac{1}{2}$ inches in diam., 3 ft. long, filled with charcoal, with an Oregon State Board of Forestry bronze cap stamped: E 1/16 C-C S24, 1949 199.

from which:

A fir snag, 43 inches in diam., bears N 83° E, a distance of 34.7 ft., scribed: BT E 1/16 S24, 199.

A location poster on a fir snag 36 inches in diam., bears S 27° E, a distance of 27.2 ft.

SUBDIVISION OF THE NE $\frac{1}{4}$ OF SEC. 24.

Beginning at the E 1/16 cor. to Secs. 13 & 24 South on a random line through the center of the NE $\frac{1}{4}$.

1389.5 Set temporary stake.

2131.2 The CE 1/16 cor. bears S 01° W, a distance of 496.6 ft.

Relative to the random line the true line through the center of NE $\frac{1}{4}$ bears S 0° 11' W, a distance of 2627.7 ft.