

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to sections 19, 20, 29, and 30, Township 3 North, Range 8 West, W.M., Tillamook County, Oregon.

ORIGINAL

Post, now missing, from which a:

- 12" Hemlock bears N66°30'E 36 lks.; now 12" stub N70E.
- 15" Hemlock bears S46°45'E 42 lks.; now 17" stub 8' high S44E.
- 24" Hemlock bears S31°45'W 56 lks.; now 24" stub 10' high S30W, scribe mark T exposed.
- 20" Hemlock bears N62°15'W 21 lks.; now 23" stub 18' high N69W.

RESTORED CORNER AND WITNESSED CORNER POINT

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T3N R8W S19 S20 S29 S30 1953 2311," 2½" in ground, from which a:

- 6" Fir bears N80°E 89.5'; scribed T3N R8W S20 BT.
- 96" Fir stump bears N48°W 59.6'; scribed T3N R8W S19 BT RE 2311.
- 3" Fir bears S64°W 6.8'; scribed S30 BT.
- 12" Fir bears S10°E 16.4'; scribed T3N R8W S29 BT.

Placed an Oregon State Board of Forestry metal location on 12" Fir BT and marked it: Sec 29 T3N R8W Sec Cor 16.4 Ft. N10°W.

Dated January 7, 1953.

This corner was restored by

Don D. Davis
Don D. Davis Assistant Forest Engineer

under my direction.



Present and witnessed by Robert A. Young, Compassman.

Robert J. Cowan, Chainman.