

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Standard section corner common to sections 33, and 34, Township 1 North, Range 8 West, W.M., Tillamook County, Oregon.

ORIGINAL

Post, now missing, from which a:

- 72" Fir bears N35E 30 lks; now 74" snag 25' high, scribe marks S34 exposed.
- 32" Hemlock bears S14E 20 lks; now 42" snag 25' high S05°E, scribe marks R8 T1S exposed.
- 14" Hemlock bears S86W 16 lks; now 17" stub 10' high S56W, scribe marks R8W T S4 exposed.
- 8" Hemlock bears N23W 57 lks; now 9" stub 20' high, exposed scribe marks T1N R8W S33 exposed.

RESTORED CORNER AND REWITNESSED CORNER POINT

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY SC T1N R8W S33 S34 S4 T1S R8W 1952 2311," 2½' in ground. Raised mound of stone around corner pipe, from which a:

- 8" Alder bears N15W 61.8'; scribed SC S33 BT.
- 60" Fir snag bears N57°45'E 81.2'; scribed T1N R8W SC S34 BT RE 2311.

Placed

Placed an Oregon State Board of Forestry metal location poster on original BT now 74" Fir snag and marked it: Sec 34 T1N R8W Standard cor 19.8 Ft. S35W.

Dated November 25, 1952.

This corner was restored by Don D. Davis  
Don D. Davis Assistant Forest Engineer

under my direction.



Present and witnessed by Robert A. Young, Compassman.

Present and witnessed by Gerald M. Schwalen, Chainman.