

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Closing corner common to sections 7 and 18, Township 1 South,  
Range 7 West, W.M., Tillamook County, Oregon.

ORIGINAL

Post, now missing, from which a:

- 24" Hemlock bears N39W 15 lks.; now 30" stub 10' high,  
exposed scribe marks BT.
- 5" Hemlock bears S28E 34 lks.; now missing.
- 20" Hemlock bears N38E 54 lks.; now missing.

RESTORED CORNER AND WITNESSED CORNER POINT

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked  
"OREGON STATE BOARD OF FORESTRY T1S S12 R8W T1S S7 S18  
CC R7W 1952 2311," 2½" in ground. Raised mound of stone  
around corner pipe, from which a:

- 48" Fir stump bears N61°30'E 43.6'; scribed T1S R7W S7  
CC BT RE 2311.
- 78" Fir snag 30' high bears S39°30'E 32.3'; scribed  
T1S R7W S18 CC BT.

Placed an Oregon State Board of Forestry metal location  
poster on 78" Fir snag BT and marked it: Sec 18 T1S  
R7W Closing cor 32.3 Ft. N39°30'W.

Dated December 2, 1952.

This corner was restored by Don D. Davis,  
Don D. Davis Assistant Forest Engineer  
under my direction.



Present and witnessed by Gerald M. Schwalen, Chainman.