

Cour Surveyor's Record, Tillamook Cour Oregon

256

T 3 S. R 8 W

Rewitnessed corners.

Mervin Whitmore, U.S. Forest Service

CHAINS

Sec. Cor.

21	22
28	27

Set 3/4" pipe, from which

- A 20" alder bears N 27° E, 13 lks. Parts of scribe marks visible after scar in old tree was chopped open. (Old BT)
- A 22" alder bears N 38° W, 36 lks. With ax scar in bark (Old BT)
- A 36" alder bears S 21° E, 48 lks. With ax scar in bark (Old BT)
- A 60" live fir, bears S. 24° E, 182 lks, slope distance. Marked T3S R8W S27 BT (New BT)
- A 30" alder bears N 41° E, 50 lks. Scribed in bark T3S R8W S22 BT (New BT)

In the presence of Wilford Fitch and
Melvin Fitch

March 15, 1952

1/4 Sec Cor.

31	32
----	----

The original stone marked 1/4 with 3/4" pipe driven alongside are about 6" below the surface of the ground near the west edge of Ed Kostic's field, from which

- A 15" maple bears S 85° W, 71 feet slope distance. Marked 1/4 S 31 BT (New BT)
- A 24" fir bears ~~W 72° E~~ N 36 1/2° E, 79.5 feet slope distance, Marked 1/4 S 32 BT (New BT)

In the presence of Ed Kostic and
Raymond Kostic

August 18, 1952