

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 2, 3, 34 and 35,
T2 & 3N, R8W, W.M., Tillamook County, Oregon.

ORIGINAL

Basalt stone 18"x19"x7", found in place with 4 notches on West
edge and 2 notches on East edge from which a:

- 10" Hemlock bears N60°E 19 lks.; just roots remaining in
place.
- 5" Maple bears S40°E 13 lks.; missing.
- 4" Maple bears S50°W 34 lks.; missing.
- 6" Yew bears N30°W 18 lks.; now 6" by 5 ft. stub, face
burnt out.

RESTORED

Erected mound of rock around original stone, from which a:

- 52" Fir stump bears N73°E 14.2 ft.; scribed T3N R8W S35
BT RE2311.
- 26" Fir snag bears N4°W 57.5 ft.; scribed T3N R8W S34 BT.
- 48" Fir stump bears S23°E 48.2 ft.; scribed T2N R8W S2 BT.
- 49" Fir stump bears S36°W 56.1 ft.; scribed T2N R8W S3 BT.

Set 4"x4"x72" white painted Cedar post 2 ft. NW of stone.
Oregon State Board of Forestry metal location poster on 52" Fir
stump BT.

Also poster on 4"x4"x72" white painted Cedar post on North edge
Cook Creek road approximately 350 ft. South of corner.

Dated October 13, 1955.

Restored by Richard A. Morris under my direction.
Richard A. Morris, Transitman



Present and witnessed by Forrest Logan
Robert Sturm
Lloyd Geraths