


Rewitnessed Corners of T3S R8W

Mervin Whitmore U.S. Forest Service

<p>CHAINS</p> <p>Sec. Cor.</p> <table border="1" style="margin-left: 20px;"> <tr> <td style="width: 20px;">26</td> <td style="width: 20px;">25</td> </tr> <tr> <td style="width: 20px;">35</td> <td style="width: 20px;">36</td> </tr> </table>	26	25	35	36	<p>Set fir limb post 36" high mkd. S25 on NE S26 on NW S35 on SW and S 36 on SE sides.</p> <p>A 12" alder bears N83°30'E, 118 lks, dist. scribe mks. visible. (Old BT)</p> <p>A 12" alder bears N61°W, 82 lks, dist. All mks. rotted out. (Old BT)</p> <p>A 50" dead fir snag bears S77°45'E. 95 lks. dist. all mks. rotted off. (Old BT)</p> <p>An 84" live fir bears N76°E 76 feet dist. mkd. T3S R8W S 25BT. (New BT)</p> <p>A 22" fir bears S72°30'E. 24.5 feet dist mkd. T3S R8W S 36BT. (New BT)</p> <p>A 16" fir bears S80°W 23 feet dist. mkd. T3S R8W S 35BT. (New BT)</p> <p>A 28" fir bears N48°W 15.5 feet dist. mkd. T3S R8W S 26 BT. (New BT)</p> <p>In the presence of Martin Chaffee and Lauris Peterson.</p> <p style="text-align: right;">March 15, 1957</p>
26	25				
35	36				
<p><math>\frac{1}{4}</math> cor.</p> <table border="1" style="margin-left: 20px;"> <tr> <td style="width: 20px;">27</td> <td style="width: 20px;"></td> </tr> <tr> <td style="width: 20px;">34</td> <td style="width: 20px;"></td> </tr> </table>	27		34		<p>The original stone mkd. <math>\frac{1}{4}</math> on N. face.</p> <p>A 60" dead fir snag bears S22°W. 71 lks. dist. mkd. <math>\frac{1}{4}</math> S. (Old BT)</p> <p>A 72" dead fir snag bears N31°30'E. 27 lks. dist. All mkd. rotted off. (Old BT)</p> <p>A 40" fir bears S54°E. 32 feet dist. mkd. <math>\frac{1}{4}</math>S 34BT (New BT)</p> <p>An 18" fir bears N78°E. 11 feet dist. mkd. <math>\frac{1}{4}</math> S 27BT. (New BT)</p> <p>In the presence of Martin Chaffee and Vern Davidson. March 18, 1957</p>
27					
34					
<p><math>\frac{1}{4}</math> cor.</p> <table border="1" style="margin-left: 20px;"> <tr> <td style="width: 20px;">35</td> <td style="width: 20px;">36</td> </tr> </table>	35	36	<p>Set a fir limb post. 3 feet high mkd. <math>\frac{1}{4}</math> S 35BT (on W) S 36 on E.</p> <p>30" fir, S41°E. 28<math>\frac{1}{2}</math> feet. slope dist. mkd. <math>\frac{1}{4}</math> S 36BT. (New BT)</p> <p>32" fir, N27°W. 30<math>\frac{1}{2}</math> feet slope dist. mkd. <math>\frac{1}{4}</math> S 35BT. (New BT)</p> <p>In the presence of Lauris Peterson. November 23, 1956.</p>		
35	36				

 <p>REGISTERED PROFESSIONAL ENGINEER                  W. A. MARKHAM                  OREGON                  May 9th 1937                  No. 1842</p>	<p>Re set this section corner, on Range line, by single proportion, on line midway between <math>\frac{1}{4}</math> Corner 24/19 and <math>\frac{1}{4}</math> Corner 13/18.</p> <p>Marked corner with a section of hexagonal drill steel 1" size, 2 feet in ground, 1 foot out of ground, and Bearing Trees:</p> <p>Alder, 6" # N64<math>\frac{1}{2}</math>°W 29.1 feet, marked S 13 1842 BT"</p> <p>Alder, 4" S48°E 22.9 feet, marked " S 19 1842 BT"</p> <p>Hemlock, 4" S30°W 13.0 feet, marked " S 24 1842 BT"</p> <p>All stake and yellow metal location poster over steel rod. Work with transit and tape.                  Done June 20, 1957.</p>
--	--