

BOUNDARY SURVEYS
 SECTIONS 17 & 18, T2N, R6W, W.M.
 TILLAMOOK COUNTY
 FOR CROWN-ZELLERBACH CORPORATION

Surveyed by Bert Mason Jr.

April--June, 1957

May 17, 1957, With Rob't. L. McCullough, I traverse southerly on a random line from the corner to sections 7, 8, 17, & 18, T2N, R6W, W.M. (Note 1) to station 24459.6 where, on May 20, 1957 I make two independent observations of the sun for bearing.

May 21, 1957, at a point near line north of the corner to sections 17, 18, 19 & 20, T2N, R6W, I set a base and observe a flag at 24439.6 for distance across Elk Creek.

May 22, 1957, from 24439.6 I set a point at the midpoint of the true line between the section corners common to sections 17 and 18 and make an extensive search for the $\frac{1}{2}$ corner. The midpoint of the line falls in a rockslide in a depression in the hillside. The surveyor stated definitely that the corner was set on the top of a "narrow rocky ridge, cs E-W". There is no original line blaze within approximately 1500 feet of this vicinity, and there is absolutely no evidence remaining of the original corner or its accessories. At least two other recent lines have been blazed, approximately 100 feet apart, one apparently due north from the southerly corner and the other apparently due south from the northerly corner.

I find a point which is due north of the southerly corner and which matches all the calls to the north and the first call to the south, and which falls on the top of a narrow, rocky ridge, cs E-W, which ends in a bluff 20 feet west of the point. No other point in the vicinity will satisfy the surveyor's description or his chainage. I set a point for the $\frac{1}{2}$ corner between sections 17 & 18 (Note 5) and traverse easterly on a random line.

May 24, 1957, at a point near the center of section 17, I set a base and observe flags at 7458.9 and 49475.5 for distance across branches of Elk Creek. I observe the sun for bearing, confirming my traverse angles; and I observe a point near the corner to sections 17, 18, 19 & 20, confirming my measurement of the south half of the line between 17 & 18. I continue my traverse easterly and tie to the $\frac{1}{2}$ corner between sections 17 & 16 (Note 5).

May 24, 1957, at the intersection of the centerlines of section 17, T2N, R6W, I set a point for the center of the section (Notes 2, 4 & 7).

May 28, 1957, at the Closing Corner between sections 18 & 19, T2N, R6W (Note 9), I chain southerly along the line between Ranges 6W and 7W to recover corners and determine the point for the $\frac{1}{2}$ corner ~~between~~ section 19, which was not set by the original surveyor (Notes 10, 11, 12 & 13).

May 30, 1957, at the Closing Corner between sections 18 & 19, T2N, R6W, I observe the sun for bearing of Range line and west half of line between sections 18 & 19.

See MAP "A-720" for plot.