

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY

Center One Quarter corner for Section 14, TLN, R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY C 1/4 SL4 1959 RS401", 48 inches in ground, covered over with dirt, and from which a:

30" Spruce bears S2 1/4 W 301.5 ft.; scribed C 1/4 SL4 BT RS401.
 E end of 18" concrete culvert bears N87 1/2 W 25.1 ft.;
 Highway center bears N87 1/2 W 43.0 ft.;

Oregon State Board of Forestry metal location poster on 30" Spruce BT.
 Also poster on 4" x 4" x 60" white painted Cedar post on W edge of highway N87 1/2 W 60.0'.

Corner point falls in a pasture.

Present and witnessed by H. Russell
 R. Cop
 E. Nylund

Center West East Southeast 1/256 corner for Section 11, (N.W. corner of the NE 1/4 NW 1/4 SE 1/4), TLN, R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E


Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY C - W - E - SE 1/256 S11 1959 RS401", 33 inches in ground, and from which a:

11" Spruce bears S21 W 52.3 ft.; scribed 1/256 S11 BT RS401.
 12" Hemlock bears N72 W 32.7 ft.; scribed 1/256 S11 BT.

Oregon State Board of Forestry metal location poster on 11" Spruce BT.
 Set 4" x 4" x 60" white painted Cedar post 1.0' S. W. of pipe.

Present and witnessed by R. Cop
 E. Nylund

Established by



Richard A. Morris
 MAY 10, 1957
 Richard A. Morris
 481