

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY

South West One Sixteenth corner for Section 11, T1N, R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY SW 1/16 S11 1959 RS401", 34 inches in ground, and from which a:

- 12" Hemlock bears S87W 7.9 ft.; scribed SW 1/16 S11 BT.
- 15" Hemlock bears N45E 4.6 Ft.; scribed SW 1/16 S11 BT RS401.

Oregon State Board of Forestry metal location poster on 9" Hemlock N18W 1.0'.

Set 4" x 4" x 60" white painted Cedar post 1.0' S.E. of corner pipe.

 North One Sixteenth corner common to Sections 11 and 12, T1N, R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY N 1/16 S11 S12 1959 RS401", 34 inches in ground, in mound of stone, and from which a:


- 26" Hemlock bears S25W 47.9 ft.; scribed N 1/16 S11 BT (by Longview Fibre Co.)
- 18" Hemlock bears N32 1/2 E 195.5 ft.; scribed N 1/16 S12 BT RS401.
- 3/4" Iron pipe bears N24°27'E 2.4 ft.; previously set by Longview Fibre Co.

Oregon State Board of Forestry metal location poster on 26" Hemlock BT.
 Set 4" x 4" x 60" white painted Cedar post 1.0' S.W. of 1 1/2" corner pipe.


Center line of road (N10E and S15E) bears East 24.0 ft.

Dated December 31, 1959

Established by



Richard A. Morris



Present and witnessed by H. Russell
 R. Cop
 E. Nylund