

County Surveyor's Record, Tillamook County Oregon

CHAINS		
--------	--	--

A F F I D A V I T

State of Oregon
County of Tillamook

I, Leonard Wallulis, of Route 1, Box 238, Nehalem, Oregon, being first duly sworn, do depose and say as follows:

I am 57 years old, and have been a timber cruiser for the last sixteen years. I saw the section corner common to sections 10, 11, 14 and 15, Township 3 North, Range 9 West, W.M., in 1947 while working for the Oregon State Board of Forestry. There was a dead Hemlock stub which I determined to be the original corner tree according to the original survey notes, and which at that time had scribes visible on it. I placed my cruiser's mark on a green Hemlock tree which was southwest about six feet from the corner tree, and found old blazes running west and north from the corner. On February 22, 1960, I returned to the location of this corner with Richard A. Morris, and found the tree with my cruiser's mark on it, and the old blazes running to the west and north, but the corner tree had been destroyed by logging. Richard A. Morris placed a 1 1/2" by 36" galvanized iron pipe with a 3" bronze cap at the point where the original corner tree was located.

Leonard Wallulis
Leonard Wallulis

STATE OF OREGON) ss
COUNTY OF TILLAMOOK)

On this 22nd day of February, 1960, before me the undersigned, a Notary Public in and for said County and State, personally appeared the within named Leonard Wallulis, who is known to me to be the identical person described in and who executed the within instrument.

William A. Phelps
Notary Public for Oregon
My commission expires 6/21/63

BOOK 2
425 (A)

X (A)
425

CHAINS

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

Section corner common to Sections 10, 11, 14 and 15, T3N, R9W, W.M., Tillamook County, Oregon.

ORIGINAL

(No evidence of original corner found)

Creek course NE bears N 250 lks.; now in place.

Creek course N bears E 380 lks.; now in place.

(See affidavit by Leonard Wallulis on file at Tillamook County Surveyor's office)

RESTORED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T3N R9W S10 S11 S15 SL4 1960 RS401", 33 inches in ground, and from which a:

20" Spruce bears S48E 25.7 ft.; scribed T3N R9W SL4 BT RS401.

14" Hemlock bears N66E 24.1 ft.; scribed T3N R9W S11 BT.

13" Hemlock bears N5W 33.5 ft.; scribed T3N R9W S10 BT.


12" Spruce bears S83W 29.3 ft.; scribed T3N R9W S15 BT.

Oregon State Board of Forestry metal location poster on 14" Hemlock BT.


Set 4" x 4" x 54" white painted Cedar post 0.7' S. W. of pipe.

Dated March 4, 1960

Restored by



Richard A. Morris



Present and witnessed by W. Phelps
L. Wallulis