

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
 West-East-East 1/256 corner common to Sections 11
 and 14 (NE Corner of NW $\frac{1}{4}$ NW $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$, Section 14), T1N,
 R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 $\frac{1}{2}$ E

Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY W-E-E 1/256 S11 S14 1959 RS401", 33 inches in ground, and from which a:

- 8" Hemlock bears N15 $\frac{1}{2}$ E 36.0 ft.; scribed W-E-E 1/256 S11 BT.
- 9" Cedar bears S13 $\frac{1}{2}$ E 37.2 ft.; scribed W-E-E 1/256 S14 BT RS401.

Oregon State Board of Forestry metal location poster on 9" Cedar BT.
 Set 4" x 4" x 60" white painted Cedar post 1.0' S.E. of pipe.

NW-NE-NE 1/256 corner for Section 14 (S.E. Corner of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$), T1N, R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 $\frac{1}{2}$ E


Set 1 $\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY NW-NE-NE 1/256 S14 1959 RS401", 33 inches in ground, and from which a:

- 17" Hemlock bears N57E 21.9 ft.; scribed 1/256 S14 BT RS401.
- 11" Spruce bears S75E 25.0 ft.; scribed 1/256 S14 BT.

Oregon State Board of Forestry metal location poster on 17" Hemlock B.T.
 Set 4" x 4" x 60" white painted Cedar post 1.0' N.E. of pipe.

Dated December 30, 1959

Established by



Richard A. Morris
 MAY 10 1967
 Richard A. Morris
 401

Present and witnessed by R. Cop
 E. Nylund