

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY  
(See official plat)  
Center East One Sixteenth corner for Section 7, T3S,  
R8W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY E 1/16 C---C S7 1960 RS401", 33 inches in ground, and from which a:

- 28" Fir bears S30 1/2 W 31.4 ft.; scribed CE 1/16 S7 BT RS401.
- 29" Fir bears N10 1/2 E 39.5 ft.; scribed CE 1/16 S7 BT.

Oregon State Board of Forestry metal location poster on 28" Fir BT.  
Set 4" x 4" x 52" white painted Cedar post 1.0' N.E. of pipe.

\* \* \* \* \*

Northeast one sixteenth corner for Section 7, T3S,  
R8W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21 1/2 E


Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY NE 1/16 S7 1960 RS401", 34 inches in ground, in mound of stone, and from which a:

- 31" Fir bears S29E 39.6 ft.; scribed NE 1/16 S7 BT.
- 28" Hemlock bears S71 1/2 W 5.9 ft.; scribed NE 1/16 S7 BT RS401.


Oregon State Board of Forestry metal location poster on 28" Hemlock BT.  
Set 4" x 4" x 52" white painted Cedar post 1.0' S.E. of pipe.

Dated November 17, 1960

Established by



*Richard A. Morris*



Present and witnessed by H. Russell  
R. Cop  
G. Nylund