

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
 (See official plat)
 Southeast One-sixteenth corner for Section 3, T1N,
 R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21½E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY SE 1/16 S3 1961 RS401", 33 inches in ground, and from which a:

18" Hemlock bears N81½E 54.2 ft.; scribed SE 1/16 S3 BT RS401.
 29" Hemlock bears N50W 36.4 ft.; scribed SE 1/16 S3 BT.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. SW of corner pipe.
 Oregon State Board of Forestry metal location poster on 29" Hemlock BT.

* * * * *

East One-sixteenth corner common to Sections 3 and
 10, T1N, R10W, W.M., Tillamook County, Oregon.

ESTABLISHED

Var. 21½E

Set 1½" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY E 1/16 S3 S10 1961 RS401", 33 inches in ground, and from which a:

15" Hemlock bears N70E 10.1 ft.; scribed E 1/16 S3 BT RS401.
 14" Hemlock bears S78W 23.1 ft.; scribed E 1/16 S10 BT.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. SE of corner pipe.
 Oregon State Board of Forestry metal location poster on 14" Hemlock BT.

Dated February 27, 1961

Established by



Richard A. Morris
 MAY 10. 1967
 Richard A. Morris
 401

Present and witnessed by H. Russell
 R. Cop
 E. Nylund