

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY

South one-sixteenth corner common to Sections 20 and 21, T3S, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY S 1/16 S20 S21 1961 RE 2311", 30 inches in ground, and from which a:

25" Fir bears S69° W 24 2/4 ft.; scribed S 1/16 S20 BT RE 2311.
18" Fir bears S63° E 27 8/8 ft.; scribed S 1/16 S21 BT.

Set 4" x 4" x 72" white painted Cedar post 1.0 ft. NE of corner pipe.

Oregon State Board of Forestry metal location poster on 16" Fir N32 1/2° E 4.8 ft.

Northeast one-sixteenth corner for Section 29, T3S, R9W, W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY NE 1/16 S29 1961 RE 2311", 32 inches in ground, and from which a:

5" Fir bears N4° W 59 3/4 ft.; scribed NE 1/16 S29 BT.
9" Alder bears N10° E 31 4/4 ft.; scribed NE 1/16 S29 BT RE 2311.

Set 4" x 4" x 72" white painted Cedar post 1.0 ft. NE of corner pipe.

Oregon State Board of Forestry metal location poster on 9" BT.

Dated June 7, 1961

Established by Billy E. Davis under my direction.
Billy E. Davis, transitman

Present and witnessed by D. McConnell
H. Baughn

Void: see plat # B-511

