

CHAINS

ESTABLISHED CORNER FOR OREGON STATE BOARD OF FORESTRY
(See official plat)
Center South One Sixteenth corner for Section 16,
T3S, R8W, W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY S 1/16 C---C S16 1961 RS401", 33 inches in ground, and from which a:

- 10" Fir bears S13E 58.6 ft.; scribed CS 1/16 S16 BT RS401.
- 15" Fir bears S37 1/2 W 64.2 ft.; scribed CS 1/16 S16 BT.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. N.E. of corner pipe. Oregon State Board of Forestry metal location poster on 10" Fir BT.

Present and witnessed by E. Nylund, A. Duncan, D. Spiesschaert

* * * * *

RESTORED CORNER FOR OREGON STATE BOARD OF FORESTRY

One Quarter corner common to Sections 16 and 21,
T3S, R8W, W.M., Tillamook County, Oregon.

ORIGINAL

Post (missing) from which a:

- 15" Fir bears N41E 30 lks.; now 36", face unexposed.
- 15" Fir bears S2 1/4 E 25 lks.; now 34", scribes 1/4 S and part of B visible, rest of face unexposed (now bears S4 1/2 E).

RESTORED

Var. 21 1/2 E

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S16 S21 1961 RS401", 33 inches in ground.


Scribed above original bearing trees BT.

Oregon State Board of Forestry metal location poster on 4" Hemlock N18E 9.0 ft.

Present and witnessed by H. Russell
G. Nylund
A. Duncan

Dated July 12, 1961

By



Richard A. Morris
MAY 10, 1957
Richard A. Morris
401

*Void
see later survey*