

CHAINS

ESTABLISHED CORNERS FOR OREGON STATE BOARD OF FORESTRY
(See official plat)
Center West One Sixteenth corner for Section 18, T3S,
R7W, W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY W 1/16 C—C S18 1961 RS401", 34 inches in ground,
and from which a:

32" Fir bears S66W 26.6 ft.; scribed CW 1/16 S18 BT RS401.
26" Fir bears N5 1/2 E 20.7 ft.; scribed CW 1/16 S18 BT.

Set 4" x 4" x 52" white painted Cedar post 1.0 ft. N.E. of corner pipe.
Oregon State Board of Forestry metal location poster on 9" Fir S12E 3.0 ft.

* * * * *

West One Sixteenth corner common to Sections 7
and 18, T3S, R7W, W.M., Tillamook County, Oregon.

ESTABLISHED

Set 1 1/2" x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE
BOARD OF FORESTRY W 1/16 S7 S18 1961 RS401", 33 inches in ground, and
from which a:

30" Fir bears S14E 46.3 ft.; scribed W 1/16 S18 BT RS401.
27" Fir bears N24W 14.0 ft.; scribed W 1/16 S7 BT.

Set 4" x 4" x 52" white painted Cedar post 1.4 ft. N.E. of corner pipe.
Oregon State Board of Forestry metal location poster on 28" Fir S25E 9.4 ft.

Dated August 17, 1961

Established by H. Russell, Transitman under my direction.

Present and witnessed by A. Duncan
D. Spiesschaert

