

July 14, 1966

NOTES FOR SETTING W 1/16 S 15/S 22 T. 4 S., R. 7 W., W.M.

Beginning at corner to Sections 15, 16, 21, and 22, which is monumented with a 3/4" x 36" Galv. I.P. alongside the original corner stone and witnessed by

- Fir 22", S 45° W, 15.0 ft.
- Fir 10", N 47° W, 9.3 ft.
- Fir 12", N 80° E, 5.8 ft.
- Fir 16", S 30° E, 54.5 ft.

S ~~W~~ E
 N 89°43' N between Secs. 15 and 22

(Meridian Reversed, Martin authorize change to SE by phone 7/19/66)

1309.20 ft. Pt. for W 1/16 S 15/S 22

Set steel axle 2" x 36" for corner from which

a fir 12", bears S 64° W, 6.0 ft. dist. marked W 1/16 Sec. 22 BT

a fir 16", bears N 83° E, 9.8 ft. dist. marked W 1/16 Sec. 15 BT

2618.39 ft. The 1/4 S 15/S 22

Which is monumented with a 3/4" x 36" Galv. I.P. and witnessed by

- Fir 42", S 16° E, 20.5 ft.
- Fir 16", N 23° W, 23.9 ft.

Witnessed by Walter R. Johnson



BOOK 3

Page 47

sec-map-B 501

BOOK 3