

## Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 7 W.

Chains	
4.90	Spur, slopes E.; desc. 240 ft. over NE. slope.
19.00	Creek, 1 lk. wide, course E.; asc. 40 ft. over SE. slope.
19.80	Point for the N 1/16 sec. cor. of secs. 22 and 23. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  N 1/16 S 22   S 23 1961  from which  A fir, 25 ins. diam., bears S. 57° E., 24 lks. dist., mkd. N 1/16 S23 BT.  A fir, 17 ins. diam., bears N. 73° W., 41 lks. dist., mkd. N 1/16 S22 BT.  Ascend 110 ft. over S. slope.
23.60	Spur, slopes E.; also SE. cor. of logged area, edge bears N. and W.; desc. 30 ft. over N. slope.
24.40	Creek, 1 lk. wide, course E.; asc. 80 ft. along broken E. slope, changing to SE. slope.
39.00	Leave logged area, edge bears SE., curving to S. and W.
39.60	The corner of secs. 14, 15, 22, and 23, monumented with the original sandstone, 12 x 12 x 8 ins. firmly set, 6 ins. in the ground, with 3 notches on N. edge and 2 grooves on the E. face. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.  T 4 S R 7 W S 15   S 14 S 22   S 23 1961  from which  A fir, 15 ins. diam., bears N. 25½° E., 178 lks. dist., mkd. T4S R7W S14 BT.  A fir, 22 ins. diam., bears S. 24° E., 41½ lks. dist., mkd. T4S R7W S23 BT.  A fir, 20 ins. diam., bears S. 31° W., 70 lks. dist., mkd. T4S R7W S22 BT.  An alder, 27 ins. diam., bears N. 45° W., 36½ lks. dist., bark scribed T4S R7W S15 BT.  Deposit the original sandstone alongside the iron post.  Land, mountainous. Soil, rocky clay. Timber, fir, alder, dogwood, and maple; undergrowth, vine maple, salal, huckleberry, salmonberry, fern, and reproduction.