

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 4 S., R. 7 W.

Chains	Descend 20 ft. over NE. slope, through heavy timber and dense undergrowth.
3.50	Bottom of descent, slopes E.; asc. 40 ft. over SE. slope.
11.00	Spur, slopes E.; desc. 80 ft. over NE. slope.
18.00	Creek, 4 lks. wide, from NW. course E.; asc. 210 ft. over broken S. slope, changing to steep SW. slope.
29.70	Spur, slopes SE.; asc. 28 ft. along E. slope, changing to SE. slope.
39.21	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 4 S R 7 W</p> <p style="margin-left: 100px;">$\frac{1}{4}$</p> <p style="margin-left: 80px;">S 15 S 14</p> <p style="margin-left: 100px;">1961</p>
	from which
	A fir, 29 ins. diam., bears S. 30° E., $13\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S14 BT.
	A fir, 31 ins. diam., bears S. 64° W., $37\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S15 BT.
	Ascend 195 ft. over broken SE. slope, changing to S. slope.
53.70	Leave heavy timber, edge bears N. and E.; enter logged area covered with scattering timber and dense undergrowth.
58.815	Point for the N $\frac{1}{16}$ sec. cor. of secs. 14 and 15. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>N 1/16</p> <p style="margin-left: 80px;">S 15 S 14</p> <p style="margin-left: 100px;">1961</p>
	from which
	A fir, 8 ins. diam., bears S. $41\frac{1}{2}^\circ$ E., 34 lks. dist., mkd. N-1/16 S14 BT.
	A fir, 37 ins. diam., bears S. 63° W., 90 lks. dist., mkd. N 1/16 S15 BT.
	Ascend 22 ft. over S. slope.
61.26	Dirt road, 15 lks. wide, bears E. and W.
62.75	Creek, 2 lks. wide, course E.; asc. 100 ft. over SE. slope.
73.20	Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.
78.42	The corner of secs. 10, 11, 14, and 15, monumented with a sandstone, now broken and weathered, 15 x 13 x 10 ins., firmly set, 10 ins. in the ground, with 2 grooves on the E. face. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.