

Subdivision of Section 31, T. 4 S., R. 7 W.

Chains	from which
	A hemlock, 12 ins. diam., bears N. 75° W., 99½ lks. dist., mkd. X BT.
	A fir, 25 ins. diam., bears S. 8½° E., 62 lks. dist., mkd. X BT.
	Witness point falls at SE. corner of timber, edge bears N. and W.
	Ascend 309 ft. over E. slope, changing to SE. slope, along the N. edge of partially logged area.
63.70	Spur, slopes S.; desc. 93 ft. over broken W. slope.
75.80	Creek, 1 lk. wide, course SW.; asc. 46 ft. along S. slope.
79.38	The ¼ sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.

Remonumentation of Certain Original Corner Points,
T. 4 S., R. 7 W.

The following field notes describe the remonumentation of certain original corner points in T. 4 S., R. 7 W., as provided for in the General Special Instructions, Group 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories When Needed".

The ¼ sec. cor. of secs. 21 and 22, monumented with the original sandstone, 14 x 12 x 6 ins., firmly set, 6 ins. in the ground, with chisel marks ¼ on W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 7 W
S 21 | S 22
1961

from which

A fir, 25 ins. diam., bears N. 75° E., 27 lks. dist., mkd. ¼ S22 BT.

A fir, 22 ins. diam., bears S. 80° W., 28 lks. dist., mkd. ¼ S21 BT.

Deposit the original sandstone alongside the iron post.

The ¼ sec. cor. of secs. 5 and 6, monumented with the original basalt stone, 20 x 12 x 8 ins., firmly set, 6 ins. in the ground, and in a mound of stone, 3 ft. base, 2 ft. high, with chisel marks ¼ on the W. face and an X on top.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.