

Dependent Resurvey, Portion of W. Bdy., T. 4 S., R. 7 W.

CHAINS

from which

A^oforked alder, 20 ins. diam., bears N. 52° E., 14 lks. dist., bark scribed N1/16 S7 BT.

A fir, 30 ins. diam., bears W. 53 $\frac{1}{2}$ lks. dist., mkd. N1/16 S12 BT.

Descend 1 ft. over gradual N. slope.

20.60 Left bank of Nestucca River, bears N. 75° W. and S. 50° E., course N. 75° W.; thence across river.

22.75 Right bank of Nestucca River, bears S. 75° E. and W.; asc. 20 ft. over SW. slope.

23.53 Power line, bears N. 65° W. and S. 65° E., curving to SE.

23.65 Gravelled road, 25 lks. wide, bears N. 65° W. and S. 65° E., curving to SE.; asc. 550 ft. over steep SW. slope.

39.20 The cor. of secs. 1, 6, 7, and 12, monumented with an iron post, 2 ins. diam., firmly set, protruding 16 ins. above the ground, with brass cap mkd. and witnessed as described in the official record of the 1933 resurvey.

The corner is located in the head of a ravine, drains SW.

Land, mountainous.

Soil, rocky clay.

Timber, fir, alder, hemlock, maple and cascara; undergrowth, vine maple, fern, salal, huckleberry, devil's club and nettle.

N. 0° 06' W., bet. secs. 1 and 6.

Ascend 180 ft. over SW. slope, through heavy timber and dense undergrowth.

6.90 Spur, slopes W.; desc. 70 ft. over NW. slope.

11.30 Creek, 1 lk. wide, course W.; asc. 20 ft. over SW. slope.

13.65 Top of ascent, slopes W.; desc. 20 ft. over NW. slope.

19.50 Dry bed of creek, 1 lk. wide, course SW.; asc. 15 ft. over S. slope.

20.13 Point for the S 1/16 sec. cor. of secs. 1 and 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 1 | S 6
1965

from which

An alder, 27 ins. diam., bears S. 25° E., 44 lks. dist., bark scribed S1/16 S6 BT.

An alder, 20 ins. diam., bears S. 30 $\frac{1}{2}$ ° W., 148 lks. dist., bark scribed S1/16 S1 BT.

Ascend 110 ft. over S. slope, changing to SW. slope.

BOOK 3