

Dependent Resurvey, Portion of W. Bdy., T. 4 S., R. 7 W.

CHAINS 30.00	Spur, slopes SW.; desc. 270 ft. over NW. slope.
38.80	Ravine, drains N. 60° W.; desc. 40 ft. over NW. slope.
40.26	The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented with an iron post, $\frac{1}{2}$ in. diam., firmly set, protruding 12 ins. above the ground, with brass cap mkd.
	$\frac{1}{4}$ S 1   S 6 1933
	from which the 1933 bearing trees:
	A fir, 28 ins. diam., bears East, 21 lks. dist., mkd. with a healed blaze.
	A fir, 32 ins. diam., bears N. 81° W., 26 lks. dist., mkd. with a healed blaze. (Record, 20 lks.)
	<hr/> N. 0° 11' W., beginning new measurement.
	Descend 50 ft. over steep rocky NW. slope.
2.30	Head of ravine, drains W.; continue along W. slope.
4.60	Wet ravine, drains S. 50° W.; asc. 115 ft. over broken SW. slope.
14.70	Spur, slopes W.; desc. 25 ft. over NW. slope.
19.75	Point for the N 1/16 sec. cor. of secs. 1 and 6.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 1   S 6 1965
	from which
	An alder, 25 ins. diam., bears S. $11\frac{1}{2}$ ° E., 87 lks. dist., bark scribed N1/16 S6 BT.
	An alder, 25 ins. diam., bears S. 57° W., 100 lks. dist., bark scribed N1/16 S1 BT.
	Descend 40 ft. over NW. slope.
21.30	Ravine, drains W.; desc. 300 ft. over NW. slope, changing to N. slope.
34.00	Ravine, drains N. 80° W.; asc. 20 ft. over SW. slope.
35.10	Top of ascent, slopes W.; desc. 15 ft. over NW. slope.
36.60	Creek, 2 lks. wide, course SW.; asc. 115 ft. over S. slope.
39.50	The cor. of Tps. 3 and 4 S., Rs. 7 and 8 W., monumented with an iron post, 3 ins. diam., firmly set, protruding 12 ins. above the ground, with brass cap mkd. and witnessed as described in the official record of the 1933 resurvey.
	The corner is located on a spur, slopes SW.