

Dependent Resurvey, Portion of W. Bdy., T. 4 S., R. 7 W.

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber; fir, alder, maple and cascara; undergrowth, vine maple, willow, salal, fern, huckleberry, devil's club and nettle.

Dependent Resurvey, Portion of N. Bdy., T. 4 S., R. 7 W.
Willamette Meridian, Oregon
(Restoring the 1873 survey by Henry Meldrum)

From the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., monumented with the original basalt stone, 15 x 10 x 10 ins., firmly set 5 ins. in the ground, mkd. $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 3 S R 7 W

$\frac{1}{4}$ S 32
S 5

T 4 S

1965

from which

A fir, 30 ins. diam., bears N. $1\frac{1}{2}^{\circ}$ E., $85\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A fir, 31 ins. diam., bears S. 19° E., $70\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S5 BT.

Deposit the original stone alongside the iron post.

N. $89^{\circ} 56'$ W., bet. secs. 5 and 32, marking and blazing the true line.

Descend 95 ft. over broken NW. slope, through scattering timber and dense undergrowth.

- 12.00 Bottom of descent, slopes N.; asc. 15 ft. over NE. slope.
- 13.70 Top of ascent, slopes N.; desc. 230 ft. over broken NW. slope.
- 31.15 Creek, 2 lks. wide, course N. 30° W.; desc. 5 ft. over NW. slope.
- 32.25 Creek, 3 lks. wide, course N. 20° W.; asc. 5 ft. over NE. slope.
- 33.20 Spur, slopes NW.; desc. 85 ft. over NW. slope.
- 38.20 Bottom of descent, slopes NW.; asc. 5 ft. over NE. slope.
- 39.43 Point for the cor. of secs. 5, 6, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.