

## Dependent Resurvey, Portion Subdivisional Lines, T. 4 S., R. 7 W.

CHAINS

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 4 S., R. 7 W., Willamette Meridian, Oregon  
(Restoring the 1873 survey by Henry Meldrum  
and 1960 resurvey by Lynn M. Roseberry)

From the cor. of secs. 20, 21, 28, 29, monmented with  
an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, protruding 6  
ins. above ground, in a mound of stone, 3 ft. base, to  
top, with brass cap mkd. and witnessed as described in  
the official record of the 1960 resurvey.

N.  $0^{\circ} 46'$  W., bet. secs. 20 and 21, marking and blazing  
the true line.

Descend 230 ft. along broken W. slope, changing to NW.  
slope, through heavy timber and light undergrowth.

19.00 Dirt road, 15 lks. wide, bears NW. and SE.

35.00 Saddle in ridge, bears N.  $20^{\circ}$  W. and S.  $20^{\circ}$  E., at inter-  
section of dirt roads, 20 lks. wide, bears NW. and SE.,  
with side road bearing S.  $5^{\circ}$  E.; asc. 15 ft. along E.  
slope, changing to SE. slope.

39.24 Point for the  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, at propor-  
tionate distance; there is no remaining evidence of the  
original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins.  
in the ground, with brass cap mkd.

$\frac{1}{4}$   
 S 20 | S 21  
 T 4 S R 7 W  
 1965

from which

A fir, 20 ins. diam., bears S.  $86\frac{1}{2}^{\circ}$  E.,  $27\frac{1}{2}$  lks.  
dist., mkd.  $\frac{1}{4}$  S21 BT.

A fir, 19 ins. diam., bears S.  $88\frac{1}{2}^{\circ}$  W.,  $82\frac{1}{2}$  lks.  
dist., mkd.  $\frac{1}{4}$  S20 BT.

The corner is located at the SE. cor. of logged area,  
edge bears N. and W.

Ascend 45 ft. over SE. slope.

46.00 Spur, slopes NE.; desc. 140 ft. over NE. slope.

55.00 Spring seepage, drains NE.; asc. 55 ft. over SE. slope.

67.00 Spur, slopes NE.; desc. 115 ft. over N. slope.

76.00 Edge of canyon, bears NW. and SE., also leave logged  
area, edge bears NW. and S.; desc. 110 ft. over steep  
rocky NE. slope.

78.48 Point for the cor. of secs. 16, 17, 20, and 21, at pro-  
portionate distance, there is no remaining evidence of  
the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in  
the rocky creek bed, with brass cap mkd.

BOOK 3