

## Dependent Resurvey, Portion of Subdivisional Lines, T. 4 S., R. 7 W.

CHAINS	
18.50	Ridge, bears NE. and SW.; desc. 115 ft. over N. slope, changing to NW. slope.
21.75	Dirt road, 15 lks. wide, bears N. 65° E. and S. 65° W.
39.70	The cor. of secs. 17, 18, 19, and 20, monumented with the original basalt stone, 15 x 12 x 8 ins., firmly set 10 ins. in the ground, mkd. with 5 notches on E. edge.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;">           T 4 S R 7 W            S 18   S 17            S 19   S 20            1965         </div>
	from which
	A fir, 18 ins. diam., bears N. 40° E., 44 lks. dist., mkd. T4S R7W S17 BT.
	A fir, 19 ins. diam., bears S. 34° E., 48 lks. dist., mkd. T4S R7W S20 BT.
	A fir, 28 ins. diam., bears S. 80° W., 14½ lks. dist., mkd. T4S R7W S19 BT.
	A fir, 21 ins. diam., bears N. 79° W., 35 lks. dist., mkd. T4S R7W S18 BT.
	Deposit the original stone alongside the iron post.
	Land, mountainous. Soil, rocky clay. Timber, fir, alder, and wild cherry; undergrowth, willow, salal, vine maple, huckleberry, Oregon grape and fern.
	From the cor. of secs. 16, 17, 20, and 21.
	N. 89° 30' W., bet. secs. 17 and 20.
	Descend 5 ft. along rocky N. slope, through scattering timber and dense undergrowth.
2.20	Creek, 3 lks. wide, course N. 30° E., enter partially logged area, edge bears SE. and W.; asc. 200 ft. over steep NE. slope.
10.00	Spur, slopes N. 10° E.; desc. 40 ft. over NW. slope.
13.20	Ravine, drains N. 15° W.; asc. 70 ft. over NE. slope.
20.30	Top of ascent, slopes N.; desc. 40 ft. over NW. slope.
22.50	Creek, 3 lks. wide, course N. 65° E.; asc. 40 ft. over SE. slope, changing to S. slope.
30.40	Same creek, 2 lks. wide, course S. 60° E.; asc. 70 ft. over NE. slope.
35.00	Dirt road, 10 lks. wide, bears NW. and SE.
39.275	Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.