

Dependent Recovery of Base Line, Portion of S. Bdy. of T. 1 N., R. 8 W.

Chains
53.28

Point for the W 1/16 sec. cor. of sec. 31 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap nkd.

W 1/16 S 31
1959

from which

An alder, 12 ins. diam., bears N. 21° E., 90½ lks. dist.,
bark scribed W 1/16 S31 BT.

An alder, 5 ins. diam., bears N. 85° W., 52 lks. dist.,
bark scribed W 1/16 S31 BT.

The corner falls on a spur sloping SW.

Descend 335 ft. over NW. slope.

66.40 Branch, 3 lks. wide, course SW.; desc. 10 ft. along S. slope.

67.94 Branch, 3 lks. wide, course SW.; asc. 237 ft. over SE. slope.

75.62 Spur, slopes S.; desc. 60 ft. over NW. slope.

77.47 Proportionate point for the closing corner of Townships 1 South, Ranges 8 and 9 West, hereinafter described.

Descend 25 ft. over NW. slope.

78.34 Wet ravine, drains SW.; asc. 6 ft. along S. slope.

78.68 Point for the corner of Townships 1 North, Ranges 8 and 9 West, restored as a point on an irregular boundary, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap nkd.

T 1 N
R 9 W | R 8 W
S 36 S 31
S 1
T 1 S R 9 W
1959

from which

A fir, 28 ins. diam., bears N. 59° E., 122 lks. dist.,
nkd. T1N R9W S31 BT.

A fir, 37 ins. diam., bears N. 54° W., 146 lks. dist.,
nkd. T1N R9W S36 BT.

The corner falls under a hemlock log, 30 ins. diam., at NE. side of a small stand of live timber.

Land, mountainous.

Soil, rocky clay with numerous rock outcroppings.

Timber, fire-killed fir, spruce, hemlock, and cedar, E. half logged; undergrowth, salmonberry, thimbleberry, huckleberry, vineapple, devil's-club, young alder, and reproduction. This mile lies at the W. edge of the Tillamook Burn.