

Dependent Resurvey of Base Line, Portion of S. Bdy. of T. 1 N., R. 9 W.

Chains	
26.65	Branch, 2 lks. wide, course N. curving to NE.; ascend 265 ft. over steep E. slope.
30.65	Spur, slopes N. 20° E.; descend 63 ft. over W. slope, changing to NW. slope.
37.78	Point for the $\frac{1}{4}$ sec. cor. of Section 4 only, on the N. bdy. of T. 1 S., R. 9 W., hereinafter described. Descend 48 ft. over NW. slope.
39.16	Point for the $\frac{1}{4}$ sec. cor. of Section 33 only, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 15 ins. in the ground, to bedrock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 1 N R 9 W $\frac{1}{4}$ S 33 <hr/> 1959
	from which
	A spruce, 14 ins. diam., bears N. 62° E., 63 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S33 BT.
	A spruce, 22 ins. diam., bears N. 81° W., 124 lks. dist., mkd. $\frac{1}{4}$ S33 BT.
	The corner falls in a slide area. Descend 138 ft. over NW. slope.
43.35	Branch, 2 lks. wide, course N.; ascend 342 ft. over NE. slope.
49.86	Spur, slopes N. 20° W.; descend 483 ft. over W. slope, changing to NW. slope.
60.90	Branch, 5 lks. wide, course N.; ascend 310 ft. over E. slope.
67.40	Spur, slopes N. 10° E.; descend 400 ft. over NW. slope.
76.34	Branch, 4 lks. wide, course N.; ascend 48 ft. over E. slope.
77.43	Point for the closing corner of Sections 4 and 5, on the N. bdy. of T. 1 S., R. 9 W., hereinafter described. Ascend 50 ft. over E. slope.
78.32	Point for the corner of Sections 32 and 33 only, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 1 N R 9 W S 32 S 33 S 5 T 1 S R 9 W 1959
	from which
	A hemlock, 17 inc. diam., bears N. 13 $\frac{1}{2}$ ° E., 56 lks. dist., mkd. T1N R9W S33 BT.