

## Dependent Resurvey of a Portion of the W. Bdy. of T. 1 S., R. 9 W.

Chains

N	1/16
S	19
1958	

from which

A spruce, 40 ins. diam., bears N. 58° E., 23 lks. dist.,  
mkd. N 1/16 S19 BT.

A fir, 26 ins. diam., bears S. 65° E., 50 lks. dist.,  
mkd. N 1/16 S19 BT.

The corner falls on a spur, slopes N. 20° W.

Descend 497 ft. over steep NE. slope.

38.16 Point for the  $\frac{1}{2}$  sec. cor. of Section 24 only, on the E. bdy. of  
T. 1 S., R. 9 W., at midpoint latitudinally.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground,  
with brass cap mkd.

T	1	S
$\frac{1}{2}$	S	24
R	9	W
1958		

from which

A hemlock, 45 ins. diam., bears S. 29° W.,  $63\frac{1}{2}$  lks. dist.,  
mkd.  $\frac{1}{2}$  S24 BT.

A hemlock, 58 ins. diam., bears N. 37° W., 88 lks. dist.,  
mkd.  $\frac{1}{2}$  S24 BT.

Descend 73 ft. over steep NE. slope.

39.50 Ravine, drains N. 50° W.; continues over NW. slope.

39.85 Branch, 4 lks. wide, course N. 50° W.; ascend 52 ft. over SW. slope.

45.34 Spur, slopes W.; descend 38 ft. over N. slope.

46.12 The corner of Sections 18 and 19 only, monumented with a basalt  
stone, 16 x 14 x 9 ins., firmly set 14 ins. in the ground, marked  
with 3 faint notches on N. and S. edges.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground,  
with brass cap mkd.

T	1	S
S	18	
S	19	
R	9	W
1958		

from which

A cedar, 11 ins. diam., bears N. 19° E., 112 lks. dist.,  
mkd. T1S R9W S18 BT.

A hemlock, 41 ins. diam., bears S. 31° E., 87 lks. dist.,  
mkd. T1S R9W S19 BT.

Deposit the basalt stone alongside the iron post.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

BOOK 3

113