

Dependent Resurvey of a Portion of the W. Bdy. of T. 1 S., R. 8 W.

Chains Point for the closing corner of Townships 1 South, Ranges 8 and 9 West, at proportionate distance longitudinally; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 1 N R 8 W
 S 31
 S 1 | S 6
 R 9 W | R 8 W
 T 1 S
 CC
 1959

from which

An alder, 6 ins. diam., bears S. $19\frac{1}{2}^{\circ}$ E., 70 lks. dist., bark scribed T1S R8W S6 CC BT.

An alder, 6 ins. diam., bears S. $23\frac{1}{2}^{\circ}$ W., 22 lks. dist., bark scribed T1S R9W S1 CC BT.

The corner falls in dense undergrowth in an area of burned and fallen timber, at S. side of wet ravine draining SW.

From this point the corner of Townships 1 North, Ranges 8 and 9 West, bears S. $89^{\circ} 35'$ W., 1.21 chs. dist., previously described.

Land, mountainous except for narrow White Creek and Little North Fork of Wilson River Valley bottoms.

Soil, rocky clay with numerous rock outcroppings and loam in the valley bottoms.

Timber, fire-killed fir, spruce, hemlock, and cedar; undergrowth, vineapple, salmonberry, thimbleberry, huckleberry, devil's-club, young alder, and reproduction. This mile lies on the W. edge of the Tillamook Burn.

Dependent Resurvey of Portion of Subdivisional Lines
 of T. 1 S., R. 9 W.

(Restoring the 1856 Survey by Samuel D. Snowden,
 the 1884 Survey by Henry Meldrum, and the
 1893 Completion Survey by Frank H. Sharp)

From the $\frac{1}{4}$ sec. cor. of Section 23 only, on the E. bdy. of Section 23, remonumented with an iron pipe, 2 ins. diam., protruding 3 ins. above ground, firmly set, in a mound of stone, 3 ft. base, 6 ins. high, at record bearing and distance from the remaining original bearing tree:

A rotted alder stub, 14 ins. diam., bears S. 60° W., 7 lks. dist., bark scribed $\frac{1}{4}$ BT.

and a local bearing tree:

A maple, 17 ins. diam., bears S. 57° W., $18\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ BT CS visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.