

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground, to bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mhd.

T 1 S R 9 W
S 2 | S 1
S 11 | S 12
1960

from which

A fir, 38 ins. diam., bears N. 49° E., 74 lks. dist.,
mhd. T1S R9W S1 BT.

A hemlock, 27 ins. diam., bears S. $37\frac{1}{2}^\circ$ E., 129 lks. dist.,
mhd. T1S R9W S12 BT.

A fir, 25 ins. diam., bears S. 57° W., 71 lks. dist.,
mhd. T1S R9W S11 BT.

A hemlock, 9 ins. diam., bears N. $59\frac{1}{2}^\circ$ W., $75\frac{1}{2}$ lks. dist.,
mhd. T1S R9W S2 BT.

Deposit the broken basalt stone alongside the iron post.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

Timber, hemlock, fir, spruce, alder, and cedar; undergrowth, vine maple, devil's-club, huckleberry, salmonberry, and reproduction.

N. $80^\circ 42'$ E., bet. secs. 1 and 12.

Descend 340 ft. over gradual E. slope, changing to steep rocky NE. slope, through heavy timber and dense undergrowth.

- 10.90 Rocky wet ravine at bottom of 50 ft. cliff, drains N. bending to NE.; asc. 10 ft. along steep rocky N. slope.
- 13.00 Top of ascent, slopes N.; desc. 130 ft. over steep NE. slope.
- 16.10 Top of cliff, 30 ft. high, edge bears N. and S.; desc. 200 ft. over steep NE. slope.
- 24.20 Point of spur, slopes N. 65° E.; desc. 328 ft. over steep E. slope.
- 29.50 Branch, 6 lks. wide, courses S. 35° E.; asc. 340 ft. over rocky SW. slope, changing to S. slope.
- 41.37 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mhd.

$\frac{1}{4}$ S 1
S 12
T 1 S R 9 W
1960

from which

A fir, 33 ins. diam., bears N. 66° W., 53 lks. dist.,
mhd. $\frac{1}{4}$ S1 BT.

A fir, 30 ins. diam., bears S. 25° W., 54 lks. dist.,
mhd. $\frac{1}{4}$ S12 BT.