

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains	Description
	Ascend 40 ft. along N. slope, through logged area covered with dense undergrowth.
6.20	Low spur, slopes NW.; desc. 254 ft. over W. slope, changing to SW. slope.
13.80	End of dirt road, 20 lks. wide, bears N.
14.76	Clear Creek, 15 lks. wide, course N.; asc. 144 ft. over E. slope, changing to SE. slope.
19.20	Point for the E 1/16 sec. cor. of secs. 3 and 10. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. E 1/16 $\frac{S\ 3}{S\ 10}$ 1958 from which A hemlock, 7 ins. diam., bears N. 13½° W., 47 lks. dist., mkd. E 1/16 S3 BT. A sawed spruce stump, 70 ins. diam., bears S. 49° W., 51½ lks. dist., mkd. E 1/16 S10 BT. Ascend 484 ft. over broken SE. slope, changing to E. slope.
28.60	Leave logged area, edge bears N. and S.; enter heavy timber and light undergrowth.
30.60	An original line tree, a hemlock, 40 ins. diam., marked with two healed hacks each on E. and W. sides.
32.20	Dirt road, 10 lks. wide, bears N. 30° E. and S. 30° W.
33.60	Spur, slopes NE.; asc. 82 ft. along N. slope.
38.40	The ¼ sec. cor. of secs. 3 and 10, determined at record distance from each of the original bearing trees, recorded and remonumented by the Oregon State Board of Forestry with an iron post, 1½ ins. diam., protruding 4 ins. above ground, firmly set, with 3 in. bronze cap mkd. Oregon State Board of Forestry ¼ $\frac{S\ 3}{S\ 10}$ 1958 from which the original bearing trees: A sawed hemlock stump, 55 ins. diam., bears N. 41° E., 40 lks. dist., with scribe marks ¼ S BT visible on opened blaze. (Record bearing, N. 55° E.) A sawed hemlock stump, 43 ins. diam., bears N. 34° W., 84 lks. dist., with scribe marks ¼ S visible on partially opened blaze. (Record bearing, N. 34½° W.) and trees marked by the Oregon State Board of Forestry in 1958: A hemlock, 15 ins. diam., bears N. 83° W., 57½ lks. dist., with scribe marks ¼ S3 BT RS401 visible on unhealed blaze. A hemlock, 9 ins. diam., bears S. 84½° E., 15½ lks. dist., with scribe marks ¼ S10 BT visible on unhealed blaze. Add marks BIM 1958 to the bronze cap.