

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains	The corner falls at edge of timber, bearing NE. and SW., and at top of ascent sloping N.					
	S. 89° 58' W., beginning new measurement.					
	Descend 193 ft. over NW. slope, changing to steep W. slope, through open logged area.					
4.65	Ravine, drains N. 20° W.; asc. 116 ft. over steep, rocky NE. slope, changing to N. slope.					
11.53	An original line tree, a sawed hemlock stump, 62 ins. diam., marked with two healed hacks each on E. and W. sides.					
13.00	Top of ascent, slopes N.; desc. 207 ft. along N. slope.					
14.00	Rocked logging road, 25 lks. wide, bears NE. and SW.					
25.50	Wet ravine, drains N. 20° E.; continue along S. edge of bottom.					
26.85	Branch, 4 lks. wide, course N. 70° E.; asc. 334 ft. over SE. slope.					
37.36	The cor. of secs. 3, 4, 9 and 10.					
	Land, mountainous. Soil, rocky clay. Timber, logged except for a stand of hemlock, fir, and spruce, near $\frac{1}{4}$ sec. cor.; undergrowth, salmonberry, huckleberry, and reproduction, E. half, open W. half.					
	N. 1° 37' E., bet. secs. 3 and 4.					
	Ascend 118 ft. over SE. slope, through open logged area.					
3.20	Spur, slopes E.; desc. 76 ft. over NE. slope.					
6.70	Ravine, drains E.; asc. 125 ft. over SE. slope.					
10.30	Leave open logged area, edge bears E. and W.; enter heavy timber and light undergrowth.					
10.90	Ridge, bears E., curving to NE., and W., curving to SW.; desc. 190 ft. over N. slope.					
15.70	Wet ravine, drains NE., curving to N; desc. 160 ft. over NE. slope.					
19.185	Point for the S 1/16 sec. cor. of secs. 3 and 4.					
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.					
	<table style="margin-left: auto; margin-right: auto;"> <tr><td>S 1/16</td></tr> <tr><td style="text-align: center;"> </td></tr> <tr><td>S 4 S 3</td></tr> <tr><td style="text-align: center;"> </td></tr> <tr><td>1959</td></tr> </table>	S 1/16		S 4 S 3		1959
S 1/16						
S 4 S 3						
1959						
	from which					
	A hemlock, 30 ins. diam., bears N. 15° E., 107 lks. dist., mkd. S 1/16 S3 BT					
	A hemlock, 45 ins. diam., bears S. 47° W., 75 lks. dist., mkd. S 1/16 S4 BT.					
	The corner falls near a branch, 1 lk. wide, course N. 15° W.					
	Descend 150 ft. over steep, broken NW. slope.					