

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains

A hemlock, 17 ins. diam., bears S. 35° W., 78½ lks. dist.,
mhd. T18 R9W S4 CC BT.

From this point the cor. of secs. 33 and 34, only, on the S. bdy. of
T. 1 N., R. 9 W., bears N. 89° 11' W., 1.87 chs. dist., previously
described.

Land, Mountains.

Soil, rocky clay with rock outcroppings.

Timber, hemlock, fir, spruce, alder, and cedar; undergrowth, devil's-
club, vine maple, salmonberry, huckleberry, sword fern, and
reproduction.

To complete the survey of sec. 3, I return to the $\frac{1}{4}$ sec. cor. of
sec. 34 only, on the S. bdy. of sec. 34, T. 1 N., R. 9 W., and run
S. 89° 11' E., along the N. bdy. of sec. 3.

2.105 Point for the $\frac{1}{4}$ sec. cor. of sec. 3 only, at midpoint in departure
on the N. bdy. of sec. 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground,
in a mound of stone, 3 ft. base, to top, with brass cap mhd.

T 1 S R 9 W
1959

from which

A fir, 26 ins. diam., bears S. 23° E., 31 lks. dist.,
mhd. $\frac{1}{4}$ S3 BT.

A fir, 16 ins. diam., bears S. 62½° W., 38½ lks. dist.,
mhd. $\frac{1}{4}$ S3 BT.

The corner falls in a slide area.

From the cor. of secs. 9, 10, 15, and 16.

N. 86° 49' W., bet. secs. 9 and 16.

Descend 100 ft. over steep W. slope, through scattering timber and
dense undergrowth.

2.20 Bottom of steep descent, drains SW.; desc. 50 ft. along S. slope.

6.50 Spur, slopes SW.; desc. 200 ft. over NW. slope.

13.50 Branch, 3 lks. wide, course SW.; asc. 10 ft. along S. slope.

19.883 Point for the E 1/16 sec. cor. of secs. 9 and 16.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground,
with brass cap mhd.

E 1/16 $\frac{S 9}{S 16}$
1960

from which

A fir, 11 ins. diam., bears N. 37° E., 24 lks. dist.,
mhd. E 1/16 S9 BT.

A hemlock, 8 ins. diam., bears S. 85° E., 39 lks. dist.,
mhd. E 1/16 S16 BT.