

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains	Descend 310 ft. over SW. slope.
29.20	Dirt road, 15 lks. wide, bears N. and S.
31.20	Branch, 4 lks. wide, course SW.; asc. 60 ft. over SW. slope, changing to S. slope.
39.77	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T 1 S R 9 W</p> <p><math>\frac{1}{4} \frac{S 9}{S 16}</math></p> <p>1960</p>
	from which
	An alder, 15 ins. diam., bears N. $18^\circ$ W., 32 lks. dist., bark scribed $\frac{1}{4}$ S9 BT.
	An alder, 12 ins. diam., bears S. $16^\circ$ W., 73 lks. dist., bark scribed $\frac{1}{4}$ S16 BT.
	Descend 110 ft. along S. slope, changing to SW. slope.
54.00	Branch, 4 lks. wide, course S.; asc. 20 ft. along general S. slope.
59.00	Branch, 1 lk. wide, course SE.; asc. 30 ft. over NE. slope.
59.655	Point for the W $\frac{1}{16}$ sec. cor. of secs. 9 and 16.  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>W <math>\frac{1}{16}</math> <math>\frac{S 9}{S 16}</math></p> <p>1960</p>
	from which
	A hemlock, 32 ins. diam., bears N. $34^\circ$ W., 61 lks. dist., mkd. W $\frac{1}{16}$ S9 BT.
	A hemlock, 22 ins. diam., bears S. $41\frac{1}{2}^\circ$ W., 53 lks. dist., mkd. W $\frac{1}{16}$ S16 BT.
	Ascend 200 ft. over E. slope, changing to SE. slope.
71.00	Spur, slopes S.; desc. 50 ft. over SW. slope.
79.54	The cor. of secs. 8, 9, 16, and 17, determined at record bearing and distance from the remains of the original bearing trees:  A stump hole, bears S. $11^\circ$ E., 80 lks. dist.  A rotted spruce stump, bears S. $28^\circ$ W., 135 lks. dist., with no scribe marks remaining.  A stump hole, bears N. $54^\circ$ W., 80 lks. dist.  At the corner point  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.