

Dependent Resurvey of Portion of Subdivisional Lines of T. 1 S., R. 9 W.

Chains

A fir, 38 ins. diam., bears S. $51\frac{1}{2}^{\circ}$ E., $70\frac{1}{2}$ lks. dist.,
 mkd. $\frac{1}{4}$ S9 BT.
 A hemlock, 33 ins. diam., bears S. $58\frac{1}{2}^{\circ}$ W., 104 lks. dist.,
 mkd. $\frac{1}{4}$ S8 BT.
 Deposit wooden stake alongside iron post.

W. $1^{\circ} 18'$ W., beginning new measurement.

Descend 30 ft. over NE. slope.


1.00 Coal Creek, 8 lks. wide, course N. 75° W.; asc. 310 ft. over SW. slope.

11.15 Spur, slopes SW.; desc. 150 ft. over NW. slope.

15.80 Branch, 2 lks. wide, course S. 70° W.; asc. 100 ft. over SW. slope.

19.88 Point for the N 1/16 sec. cor. of secs. 8 and 9.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 17 ins. diam., bears S. $28\frac{1}{2}^{\circ}$ E., 39 lks. dist.,
 mkd. N 1/16 S9 BT.

A fir, 14 ins. diam., bears N. $44\frac{1}{2}^{\circ}$ W., $18\frac{1}{2}$ lks. dist.,
 mkd. N 1/16 S8 BT.

Ascend 260 ft. over SW. slope.

31.30 Wet ravine, drains SW.; asc. 400 ft. over steep, rocky S. slope.

39.76 Point for the cor. of secs. 4, 5, 8, and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, to bedrock, with brass cap mkd.



from which

A fir, 10 ins. diam., bears East, $19\frac{1}{2}$ lks. dist.,
 mkd. T1S R9W S4 BT.

A fir, 18 ins. diam., bears S. 6° E., 50 lks. dist.,
 mkd. T1S R9W S9 BT.

A fir, 17 ins. diam., bears S. 82° W., 26 lks. dist.,
 mkd. T1S R9W S8 BT.

A fir, 8 ins. diam., bears N. 62° W., 31 lks. dist.,
 mkd. T1S R9W S5 BT.

Corner point falls on rock outcropping.