

CHAINS

Page 10.

T4SR8-9W (cont.)

distances but all marks are rotted off. I set up the original post which is in a fair state of preservation.

I marked 4 new BTs:  
 20" fir, N.34°W., 19ft. Mkd. T4SR9WS12 BT  
 20" fir, N.53°E., 12ft. Mkd. T4SR8WS7 BT  
 18" fir, S.39°E., 5ft. Mkd. T4SR8WS18 BT  
 28" fir, S.40°W., 40ft. Mkd. T4SR9WS13 BT

This corner is south 50ft. from the head of a canyon bearing N.

Witnesses: Hobart Means  
 M. Whitmore

by Leonard Whitmore,  
 Tillamook Co. deputy surveyor  
 9-4-61

EVALUATION AND RESTORATION OF LAND SECTION CORNERS

T4SR8W

18   17	Section corner to sections; 17,18,19,20 Original Monument 18x14x8 basalt stone with 3 notches on S. and 5 notches on east edge.
19   20	

Original Witnesses:  
 30" fir, N.54°W., 59 Lks Mkd. T4SR8WS18 BT  
 22" fir, N.37°E., 58 Lks. Mkd. T4SR8WS17 BT  
 38" fir, S.48°E., 83 Lks Mkd T4SR8WS20 BT  
 24" fir, S.53°W., 85 Lks Mkd T4SR8WS19 BT

I found 12x10x5 basalt stone 10" above ground with 3 notches on S. and 5 notches on E. edges. Found 38" snag, S.48°E., 83 Lks. With visible Mks. S820 T4SR8W. The SW, NW, and NE BTs are in their recorded bearings and distances but all marks are rotted away. Found the original E-W and N-S blazes intersecting at the corner point.

I marked 4 new witnesses:  
 29" fir, N.40°W., 27 Lks Mkd T4SR8WS18 BT  
 36" fir, S.82°W., 44 Lks Mkd. T4SR8WS19 BT  
 12" fir, S.31°E., 26 Lks Mkd T4SR8WS20 BT  
 22" fir, N.58E., 37 Lks Mkd T4SR8WS17 BT